



VISON FLOOR MUD

Portland Cement Mortar Bed

Product Name: VISON FLOOR MUD

Manufacturer: Vison Tech Products LLC

Product Description:

VISON FLOOR MUD is a professional blend of Portland cement and graded sands, that have been formulated to create an optimized mortar bed. Used for tile and stone installations at 1.25 -2" of thickness to facilitate accurate slopes and planes in finished tile work. The factory blend provides a consistent and durable product. The pre-blend package is more consistent and reliable product over a job-site/field mix method.

Packaging

COLOR: Gray

TEXTURE: Powder consisting of Portland cement, washed and graded silica sand.

PACKAGING: 50 lbs. Multi-wall bags.

Basic Use:

VISON FLOOR MUD is mortar mix used for leveling or sloping substrates. Use the factory pre-blend mortar for industrial, commercial and residential installations. Use for installations specifying mortar bed or deck mud. Use VISON FLOOR MUD in reinforced, unbonded or bonded mortar bed applications. This product lowers labor costs and increases installation productivity. For exterior or heavy-duty application use VISON POLY MUD.

Key Benefits and Features

- Optimized factory blend
- Excellent compressive strength
- Pre-blend, eliminates job site blending of powders
- Increased production
- Economical, reduces cost and saves time

Suitable Tile Types

Vitreous and semi-vitreous tile: ceramic, mosaic, quarry, impervious porcelain, brick and thin brick; cement-based precast terrazzo and natural stone tile.

Limitations

Not for loose or weak surfaces subjected to deflection greater than 1/360th of span. This product is impervious to water but does not form a waterproof or moisture barrier. For exterior, wet or freeze-thaw applications use VISON POLY MUD. Do not allow mortar bed application to freeze for the first 72 hours of cure. Temperature of area to be installed must remain above 50°F (10°C) for 72 hours.

Applicable Standards

Meets and exceeds requirements for mortar beds application within the TCNA Handbook details and ANSI A108.1A, A108.1B and A108.1C

Installation: Mixing

For best results, maintain all materials, substrates, room and adhesives at 50°-70°F (10-21°C) for 24 hours before and 72 hours after installation. In a clean mixing container, add 50 lbs. (22.68 kg) VISON FLOOR MUD with approximately ½ gallons (1.8 L) clean, cool water. Mix material to a damp consistency that allows tight compaction with the minimal amount of water. The mix should appear as a moist, granular dry-packable mixture that does not flow or slump.

General Surface Prep

All surfaces must be stable, rigid and structurally sound. Concrete must be fully cured, not weak or deteriorated. Remove loose or poorly bonded surface materials. Concrete and wood framing system/flooring substrate must be structurally sound and meet all ANSI and deflection requirements. Ambient temperature should be maintained above 50°F (10° C) or below 100°F (38° C) for 72 hours to achieve proper cure. Concrete, masonry, wood, plywood, foam insulation board and substrates must support the mortar bed weight and final finished covering for both live and dead loads. For "bonded mortar bed", substrate must be free of all grease, oil, dust, dirt, curing compounds, sealers, coatings, efflorescence, Cut-back adhesive residue, gypsum based underlayment, foreign or anti-adherent matter. For exterior or heavy duty application use VISON POLY MUD polymer-latex modified, pre-blend mortar.

Vison Tech Products
6464 Cunningham Road
Houston, TX 77041
Phone: (832) 850 - 6085

fax: (281) - 258 - 4114
www.visontechproducts.com
sales@visontechproducts.com
techsupport@visontechproducts.com



VISON FLOOR MUD

Portland Cement Mortar Bed

Expansion Joints

Install expansion joints around all perimeters or restraining surfaces where possible to allow for expansion movement. Expansion joints and cold joints, as described in ANSI A108.01, should never be bridged with setting material. They must be brought through the tile work and filled with an appropriate elastomeric sealant. Contact Vison Tech's Technical Services for the proper treatment of control or saw cut joints. Refer to TCNA EJ171, F125 & F125A.

Showers

Use VISON FLOOR MUD at 1.25" minimum on the receptors. Showers require approved waterproof membrane and reinforcement. Consult building codes, ordinances and local trade practices.

Application

Apply to a thickness of 1.25"- 2.0" (32-50mm) thickness as mortar bed for direct bond floors application.

Rub, brush and trowel slurry bond coat into the concrete substrate. The slurry application must be completely wet (not dry/damp) when applying VISON FLOOR MUD; maintain a fresh, wet primer coat on the floor. Use screed guides or float strips to screed mortar to the necessary surface tolerances. Slope the mortar where necessary to the drains. Immediately apply VISON FLOOR MUD over the slurry cement coating. Firmly tamp and screed the VISON FLOOR MUD.

For "unbonded mud beds", place cleavage membrane in accordance to ANSI A108.02-3.8 such as 15-lb. roofing felt or 4 mil. polyethylene film over the concrete. Apply VISON FLOOR MUD and reinforcing over the membrane. Embed corrosion resistant reinforcing that complies with ANSI A108.02 - 3.6 or 3.7. Lap reinforcing mesh by minimum of one mesh opening. Raise the reinforcing to be within the middle of the VISON FLOOR MUD. Keep reinforcing mesh away from abutting against vertical surfaces. Compact/tamp and screed to desired level or proper slope to drain if required. VISON FLOOR MUD shall be 1.25" thick nominal.

Coverage

Per 50 lbs. (22.7 kg) bag yields 5 ft² at 1.25 " (38mm) thickness.

Specifications: Technical Data

| Test | Typical Values |
|---|----------------------------|
| Bucket life @ 70°F | 90 to 120 minutes |
| Application temperature range | 40°F to 95°F (4°C to 35°C) |
| Compressive strength (ASTM C109, 28 days) Mixed with water | > 2,500 psi (17.2 MPa) |

Storage Life

One year if kept dry in sealed bag.

KEEP OUT OF REACH OF CHILDREN

Warranty

Vison Tech warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Vison Tech's sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Vison Tech's printed instructions. Vison Tech makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another.

Vison Tech Products
6464 Cunningham Road
Houston, TX 77041
Phone: (832) 850 - 6085

fax: (281) - 258 - 4114
www.visontechproducts.com
sales@visontechproducts.com
techsupport@visontechproducts.com